

MAIN FEATURES AND BENEFITS:

- The Latest Generation Peristaltic Hose in FDA Food Grade Nitrile and Food Grade Internal Lubricant.
- Ease of Disassembly of the Front Cover and Removal of the Roller, to aid CIP Cleaning Processes.
- Stainless Steel Base Plate and Front Cover.
- The DIN 11851 or Tri-Clamp Stainless Steel Connections to Facilitate CIP Cleaning Processes.

TMVT F12 | F17 | F21

TECHNICAL SPECIFICATIONS	MODEL F12
Max. Flow (continuous)	180 l/h
Capacity	0,037 l/rev
Max. Discharge Pressure	10 bar
Max. Temperature	80 °c
Inner Diameter	13 mm.
Hose material	NBR (Food Grade)
Connections	AISI-316
Pump casing material	Cast Iron (Powder Coated)

TECHNICAL SPECIFICATIONS	MODEL F17
Max. Flow (continuous)	450 l/h
Capacity	0,094 l/rev
Max. Discharge Pressure	10 bar
Max. Temperature	80 °c
Inner Diameter	16 mm.
Hose material	NBR (Food Grade)
Connections	AISI-316
Pump casing material	Cast Iron (Powder Coated)

TECHNICAL SPECIFICATIONS	MODEL F21
Max. Flow (continuous)	1200 l/h
Capacity	0,246 l/rev
Max. Discharge Pressure	10 bar
Max. Temperature	80 °c
Inner Diameter	22 mm.
Hose material	NBR (Food Grade)
Connections	AISI-316
Pump casing material	Cast Iron (Powder Coated)

TMVT F28 | F35

TECHNICAL SPECIFICATIONS	MODEL F28
Max. Flow (continuous)	1600 l/h
Capacity	0,376 l/rev
Max. Discharge Pressure	10 bar
Max. Temperature	80 °c
Inner Diameter	28 mm.
Hose material	NBR (Food Grade)
Connections	AISI-316
Pump casing material	Cast Iron (Powder Coated)

TECHNICAL SPECIFICATIONS	MODEL F35
Max. Flow (continuous)	3200 l/h
Capacity	0,748 l/rev
Max. Discharge Pressure	10 bar
Max. Temperature	80 °c
Inner Diameter	35 mm.
Hose material	NBR (Food Grade)
Connections	AISI-316
Pump casing material	Cast Iron (Powder Coated)

TMVT F43 | F55

TECHNICAL SPECIFICATIONS	MODEL F43
Max. Flow (continuous)	6500 l/h
Capacity	1,537 l/rev
Max. Discharge Pressure	10 bar
Max. Temperature	80 °c
Inner Diameter	43 mm.
Hose material	NBR (Food Grade)
Connections	AISI-316
Pump casing material	Cast Iron (Powder Coated)

TECHNICAL SPECIFICATIONS	MODEL F55
Max. Flow (continuous)	13000 l/h
Capacity	3,533 l/rev
Max. Discharge Pressure	10 bar
Max. Temperature	80 °c
Inner Diameter	55 mm.
Hose material	NBR (Food Grade)
Connections	AISI-316
Pump casing material	Cast Iron (Powder Coated)